



UC2000-VG(V133) GSM/WCDMA/LTE VoIP Gateway

Dinstar UC2000-VG GSM/WCDMA/LTE VoIP Gateway is a multi-functional product used to effectively implement the smooth transition between PLMN (Mobile) and VoIP network. The UC2000-VG gateway is designed for comfort, ease-of-use to satisfied necessary of customers. It is not only inherits tradition of quality voice communication over IP network but reduce the human resource of VoIP network deployment. It's a cost-effective gateway for call termination (VoIP to GSM) and origination (GSM to VoIP). It is fully compatible with leading Soft-switch and SIP server.

Product Pictures



Key Features

- 32 GSM Channels with 128 SIM Slots, Easy to Conduct SIM Rotation Locally
- GSM: B3/B8; WCDMA: B1/B5/B8; LTE FDD: B1/B3/B5/B7/B8/B20; LTE TDD: B38/B40/B41
- Built-in Bandwidth Saving, Signaling & RTP Encryption
- HTTP API for Bulk SMS
- Auto Call/SMS Generation
- Auto Update SIM Number and Balance Check
- No Balance Alarm and Call Minutes Limitation

Honesty Concentration

Voice Processing

- Protocol: SIP v2.0, RFC3261
- Codecs:G.711A/U law, G.723.1, G.729A/B
- Silence Suppression
- Comfort Noise Generator(CNG)
- Voice Activity Detection(VAD)
- Echo Cancellation: G.168 with up to 128ms
- Dynamic Jitter Buffer
- DTMF: RFC2833, SIP Info
- Call Progress Tone Generation
- Programmable Gain Control
- NAT: STUN, Dynamic NAT, Static NAT

Mobile

- SIM Interface: 1.8v, 3.0v SIM Interface
- Frequency Range:
 - GSM: B3/B8; WCDMA: B1/B5/B8;
 - LTE FDD: B1/B3/B5/B7/B8/B20;
 - LTE TDD: B38/B40/B41
- USSD Encoding: Unicode/ASCII
- HTTP API for SMS
- Polarity Reversal
- PIN Modify
- Carrier Auto/Manual Selection
- CID/CLIR
- BCCH
- SMS Send and Receive
- SMS to Email
- Call Waiting/Call Back
- Call Forward
- GSM Audio Coding: HR, FR,EFR,
AMR_FR,AMR_HR

Software Features

- Calling Type:
 - Mobile to VoIP, VoIP to Mobile
- SIP Trunk and Trunk Group
- Caller/Called Number Manipulation Rules
- SIP Codes Mapping
- White/Black List
- PSTN Hotline
- VoIP Hotline
- Password authentication for incoming and outgoing calls
- Abnormal Call Monitor
- Call Minutes Limitation for Ports/Single Call
- Auto SMS/Call Generation
- Balance Check
- Low Balance Alarm
- Auto Update SIM Number
- Random Call Interval
- Abnormal Call Monitor
- SIM Rotating by
 - SIM Run Time
 - SIM Balance
- Bandwidth Saving
- Signaling & RTP Encryption
- VOS RC4 Encryption

Innovation Open-mind

Network

- Static IP, DHCP Client, PPPoE
- Network Protocols:
 - TCP/UDP, TFTP, FTP, RTP/ RTCP,
 - SSH, ARP, RARP, ICMP Ping, NTP, HTTP, DNS
- Static/Dynamic ARP Request

Maintenance

- Web/Telnet Configuration
- Configure Backup/Restore
- Firmware Upgrade by HTTP/TFTP
- Factory Reset
- CDR (10000 Lines CDRs Storage Locally)
- Syslog/Filelog
- Ping and Tracert
- Traffic statistics: TCP, UDP, RTP
- VoIP Call Statistics
- PSTN Call statistics: ASR, ACD, PDD
- Voice Dialogist with Loopback
- GSM Network Dialogist
- IVR Customization
- Auto Provisioning
- SIP/RTP/PCM Capture

Physical Interface

- Mobile: 32 GSM Channels
- SIM Card Slots: 128
- Ethernet Interfaces:
 - 2*10/100 Base-T, RJ45
- LED Indicators: Power, RUN, Signal Strength Indicators
- Console:
 - 1* RS232 115200bps

Environmental

- Power Supply:
 - 100-240VAC, 50-60Hz
- Power Consumption: 68w
- Operating Temperature: 0 °C ~ 40 °C
- Storage Temperature: -20 °C ~ 80 °C
- Humidity: 10%-90% Non-Condensing
- Dimensions(W/D/H): 440×270×75mm
- Unit Weight: 4.7kg

Shenzhen Dinstar Technologies Co., Ltd.

9th Floor, Guoxing Building, Changxing Road, Nanshan District, Shenzhen,
Guangdong, P.R.China, 518052

Tel.: +86 755 6191 9966 FAX: +86 755 2645 6659

Email: sales@dinstar.com support@dinstar.com

Website: www.dinstar.com